

SPECIAL PROVISIONS



Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Contains phthalic anhydride. May produce an allergic reaction. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges. Do not breathe vapours. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep container tightly closed.



UN 1866

QR CODE



<https://my.chemius.net/p/ft7Dfz/en/pd/e8>

SAFETY PRECAUTIONS



Personal protective equipment: always use personal protective equipment while handling the product.

Hand protection: Protective gloves (BS EN ISO 374). The penetration time is determined by the protective glove manufacturer and must be observed. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Material: Neoprene, Material: Nitrile, Material: Viton (fluorinated rubber), Material: PVA.

Eye and face protection: Safety glasses with side protection (BS EN ISO 16321-1:2022).

Skin protection: Protective antistatic clothing BS EN 1149 (1:2006, 2:1997 and 3:2004, 5:2018), protective antistatic shoes (BS EN ISO 20345:2022+A1:2024). Wear fire/flame resistant/retardant clothing. BS EN ISO 11612:2015 - Protective clothing – Clothing to protect against heat and flame. Standard EN ISO 14116 - Limited flame spread materials Protective antistatic clothing BS EN 1149 (1:2006, 2:1997 and 3:2004, 5:2018), protective antistatic shoes (BS EN ISO 20345:2022+A1:2024).

Respiratory protection: In case of insufficient ventilation wear suitable respiratory protection. Protective masks (BS EN 136) or half masks (BS EN 140) with filter A (BS EN 14387). In case of dust formation wear appropriate protective mask - mask with particle filter. Wear suitable protective breathing mask (BS EN 136) with filter A2-P2 (BS EN 14387).





Storage: Store in accordance with local regulations. Keep in a cool, dry and well ventilated place. Keep away from heat and sources of ignition. Keep away from food, drink and animal feeding stuffs. Keep away from strong oxidising agents. Keep away from peroxides. Keep away from reducing agents.



Personal hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Appropriate technical measures to reduce exposure of workers must be chosen depending on the specific use of the product and the resulting risk of exposure at the workplace.



EMERGENCY PROCEDURES

Methods for cleaning up: Prevent release into the sewer, water, basements or confined areas. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Make sure the leakage site is well aired. Use spark-proof tools. Dispose in accordance with applicable regulations (see Section 13).

Appropriate extinguishing agent: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Alcohol-resistant foam.

Fire extinguishing powder.

Carbon dioxide (CO₂).

Warn others! See: local Fire safety plan



Provide first aid!
Protect yourself. Do not inhale gas/smoke/vapours/mist.
After an accident, wait for the superior's or the fire-fighter's permission to re-enter the work area.



Inform superiors!

SYMPTOMS OF INTOXICATION/OVEREXPOSURE

Inhalation: Coughing, sneezing, nasal discharge, labored breathing. Can cause irritation of respiratory system. Harmful.



Skin contact: Itching, redness, pain.

Eye contact: Redness, tearing, pain.

Ingestion: May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

DESCRIPTION OF FIRST AID MEASURES

Inhalation: Remove patient to fresh air - move out of dangerous area. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Obtain professional medical help!

Skin contact: Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Eye contact: Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Ingestion: Do not induce vomiting! Rinse mouth thoroughly with water. Consult a physician! Show the physician the safety data sheet or label. Never give anything by mouth to an unconscious person.

WASTE DISPOSAL CONSIDERATION

Waste disposal: Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

Disposal of the contaminated packaging: Dispose of in accordance with applicable waste disposal regulation. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Deliver completely emptied containers to approved waste disposal authorities. Empty containers represent a fire hazard as they may contain flammable product residues and vapours. Uncleaned containers should not be perforated, cut or welded.

Respect internal waste disposal instructions.