

# Tuff stuff Topcoat

Print date: 01.07.2025



Cure It Composites Ltd

## SPECIAL PROVISIONS



Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges. Do not breathe vapours. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep container tightly closed.



UN 1866

## QR CODE



<https://my.chemius.net/p/bhLDOH/en/pd/en>

## SAFETY PRECAUTIONS



**Personal protective equipment:** always use personal protective equipment while handling the product.

**Hand protection:** Protective gloves (BS EN ISO 374). Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Material: Neoprene Remark: BS EN ISO 374, Material: Nitrile Remark: BS EN ISO 374, Material: Viton (fluorinated rubber) Remark: BS EN ISO 374, Material: PVA Remark: BS EN ISO 374.

**Eye and face protection:** Safety glasses with side protection (BS EN ISO 16321-1:2022). Do not use contact lenses.

**Skin protection:** Choose body protection according to the activity and possible exposure. Cotton protective clothing and shoes that cover the entire foot (BS EN ISO 20345:2022+A1:2024). Apron (BS EN 14605:2005+A1:2009). Protective work clothing resistant to liquid chemicals (BS EN 14605:2005+A1:2009). At high risk of skin exposure chemical suits (BS EN 13034:2005+A1:2009) and boots may be required (BS EN ISO 20345:2022+A1:2024). Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. Protective antistatic clothing BS EN 1149 (1:2006, 2:1997 and 3:2004, 5:2018), protective antistatic shoes (BS EN ISO 20345:2022+A1:2024).

**Respiratory protection:** In case of insufficient ventilation wear suitable respiratory protection. Wear a suitable protective breathing mask (BS EN 136) with filter A (BS EN 14387). If dusting is occurring, use respiratory equipment. Wear suitable protective breathing mask (BS EN 136) with filter A2-P3 (BS EN 14387). For dust/gas/vapor concentrations above the

# Tuff stuff Topcoat

Print date: 01.07.2025



Cure It Composites Ltd



applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard BS EN 137, BS EN 138.



**Storage:** Store in accordance with local regulations. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition - no smoking. Keep in a cool, dry and well ventilated place. Keep away from strong oxidising agents. Keep away from peroxides. Keep away from reducing agents.



**Personal hygiene measures:** Do not breathe vapours/aerosols. Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes.



## EMERGENCY PROCEDURES

**Methods for cleaning up:** Remove all sources of ignition. Prevent release into the sewer, water, basements or confined areas. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Dispose in accordance with applicable regulations (see Section 13). Ventilate the premises. Use spark-proof tools. Use only explosion-proof instruments and equipment.

**Appropriate extinguishing agent:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Alcohol-resistant foam.

Foam. In enclosed areas: carbon dioxide.

**Warn others!:** See: local Fire safety plan



Provide first aid!  
Protect yourself. Do not inhale gas/smoke/vapours/mist.  
After an accident, wait for the superior's or the fire-fighter's permission to re-enter the work area.



Inform superiors!

## SYMPTOMS OF INTOXICATION/OVEREXPOSURE

# Tuff stuff Topcoat

Print date: 01.07.2025



Cure It Composites Ltd

**Inhalation:** Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

**Skin contact:** Itching, redness, pain. May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

**Eye contact:** Redness, tearing, pain.

**Ingestion:** May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

## DESCRIPTION OF FIRST AID MEASURES

**Inhalation:** Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If breathing is irregular or respiratory arrest occurs, provide artificial respiration. Seek medical help immediately. In case of unconsciousness bring patient into stable side position and seek medical attention.

**Skin contact:** Wash affected skin areas thoroughly with plenty of water and soap. Take off all contaminated clothing. If symptoms develop and persist, seek medical attention.

**Eye contact:** Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

**Ingestion:** Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediately consult a doctor. Show the physician the safety data sheet or label.

## WASTE DISPOSAL CONSIDERATION

**Waste disposal:** Dispose of in accordance with applicable waste disposal regulation. Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

**Disposal of the contaminated packaging:** Dispose of in accordance with applicable waste disposal regulation. Cleaned uncontaminated packaging may be taken for recycling. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapours. Deliver completely emptied containers to approved waste disposal authorities.

Respect internal waste disposal instructions.